

FLY-1201

iNetVu®
by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The new model of iNetVu® 1.2m Flyaway Antenna System is a highly portable, self-pointing, auto-acquire unit that is configurable with the iNetVu® 7024B/C controller and can be assembled in less than 15 minutes by one person. The antenna features a 2-piece segmented glass fibre reinforced reflector with compact pedestal and is designed to be value priced while providing exceptional performance in a light weight package.



Features

- One button auto-pointing controller
- 3 Axis motion
- Airline transportable
- Supports manual control when required
- Designed to work with the iNetVu® 7024B/C Controller
- Captive hardware / fasteners
- 1.2m offset, prime focus, 2-piece thermoset molded reflector
- Carbon fibre reflector available in 1 piece, 2 pieces & 4 pieces
- Supports Skyware 1.2m antenna, Type 125
- No tools required for assembly / disassembly
- Less than 15 minutes assembly time, one person job
- Elevation-over-azimuth pedestal provides excellent stiffness characteristics and convenience for the user
- Eutelsat / Intelsat compliant
- Compact packaging, 4 ruggedized shipping cases
- Minimal maintenance required
- 2 Year Warranty

Application Versatility

The FLY-1201 Flyaway System is easily configured to provide instant access to satellite communications for any application that requires reliable and/or remote connectivity in a rugged environment. Ideally suited for industries such as Disaster Management, Military, Oil & Gas Exploration, Mining, Construction, Mobile Offices and Emergency Services.

C-COM
SATELLITE SYSTEMS INC.

www.c-comsat.com
613-745-4110 | 877-463-8886

Specifications are subject to change

Apr 2012

FLY-1201

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Antenna size	1.2m
Reflector Material	Glass fibre reinforced polyester ⁽¹⁾
Optional	Carbon Fibre
Mount Geometry	Elevation over azimuth
Antenna optics	2-piece segmented, Offset feed prime focus
Optional	1-piece & 4-piece segmented
Offset angle	16.97°
Azimuth	±180°
Elevation	5° to 90°
Polarization	±90°
Elevation deploy speed	Variable 6° / sec
Peaking speed	0.2° / sec

Environmental

Wind loading	
Operational	
No ballast or anchors	48 km/h (30 mph)
With ballast or anchors	72 km/h (45 mph)
Survival (with ballast)	145 km/h (90 mph)
Solar radiation	360 BTU / h / sq. ft
Temperature	
Operational	-30° to 55° C (-22° to 131° F)
Survival	-40° to 65° C (-40° to 149° F)
Rain	
Operational	10 cm/h
Survival	15 cm/h

Electrical

Electrical interface	24VDC 8 Amp (Max.)
Rx & Tx cables	2 RG 6 cables (10m each)
Control cables	
Standard	10m (33 ft) ext. cable
Optional	up to 30m (100 ft) available

RF Interface

Radio mounting	Feed arm
Coaxial	RG6U F type (N type optional)

Cases

Case 1: 2-piece reflector	130 x 29.5 x 75 cm (51.2" x 11.6" x 29.5") 33.5 kg (73.7 lbs)
Case 2: Feed arm	20.6 x 55.2 x 24.7 cm (47.5" x 21.7" x 9.7") 20.5 kg (45.1 lbs)
Case 3: Tripod	95 x 69 x 37 cm (37.4" x 27.2" x 14.5") 42 kg (92.4 lbs)
Case 4: 6U rack mount	32 kg (70 lbs)

Ku-Band

Transmit Power	1 to 200 watt	
Polarization	Linear, Orthogonal	
	Receive	Transmit
Frequency (GHz)	10.70-12.75	13.75-14.50
Feed interface	WR75	WR75
Efficiency	70%	70%
Midband gain (± .2 dBi)	41.8 dBi	43.3 dBi
Antenna Noise Temp. (K)		
10° Elevation	45	
30° Elevation	24	
Sidelobe better than		
	1.5° <Θ < 20°	29 - 25 LogΘ dBi
	20° <Θ < 26.3°	-3.5 dBi
	26.3° <Θ < 48°	32 - 35 LogΘ dBi
	48° <Θ < 180°	-10 dBi
Cross Polarization on axis	30 dB	35 dB
Within 1 dB beamwidth	30 dB	30 dB
VSWR	1.3:1	1.3:1
Tx/Rx isolation	>40 dB	90 dB
Feed	2port Xpol	

Shipping Weights & Dimensions

Transportable Case and Reflector:
Tripod Case: 97 cm x 71 cm x 38 cm (38" x 28" x 15"), 45 kg (100 lbs)
Feed Arm Case: 120 cm x 56 cm x 25 cm (47" x 22" x 10"), 20.5 kg (45 lbs)
Reflector Case: 132 cm x 31 cm x 76 cm (52" x 12" x 30"), 34 kg (74 lbs)
Controller Case: 71 cm x 51 cm x 74 cm ((28" x 20" x 29"), 36 kg (80 lbs)
Total including pallet:
140 cm x 140 cm x 104 cm (55" x 55" x 41"), 160 kg (353 lbs)

Note:

⁽¹⁾ Antenna based on Skyware, Model 125.



www.c-comsat.com
613-745-4110 | 877-463-8886

Specifications are subject to change

Apr 2012